



# AUTOGEAR OIL MP 85W-140

## Product Description:

**AUTOGEAR OIL MP 85W-140** is a universal high performance mineral multi-purpose gear oil for use in manual transmission en transaxles of passenger cars, vans, light- and heavy commercial vehicles, off-highway equipment, mining and agriculture where a SAE 85W-140 GL-5 is been required.

**AUTOGEAR OIL MP 85W-140** is based on high quality mineral base oil in combination with a special additive package to ensure the following properties:

- Good thermo-oxidative stability.
- Good load bearing characteristics.
- Effective rust and corrosion protection.
- High low temperature fluidity provides smoother shifting at low ambient temperatures.
- Exceptional shear stable.

**AUTOGEAR OIL MP 85W-140** meets the following performance criteria:

**API GL-5 MIL-L-2105D**



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J306	85W-140
Density@15°C	kg/m <sup>3</sup>	ASTM D4052	906
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	414
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	29.0.
Low-Temperature Brookfield Viscosity @ -12°	cP	ASTM D2983	100000
Viscosity Index		ASTM D2270	99
Flash Point	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-15

**Product Nr:** 43080

**Date Superseded:** 21-02-2018

**Date Issued:** 13-12-2019

**Revision nr:** 02