

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form : Mixture  
Product name : 43110 - AUTOGEAR OIL XP 80W-90  
Product code : 43110  
Type of product : Lubricant  
Product group : Industrial

**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.2.1. Relevant identified uses**

Main use category : Industrial use, Professional use  
Industrial/Professional use spec : For professional use only  
Industrial

**1.2.2. Uses advised against**

No additional information available

**1.3. Details of the supplier of the safety data sheet**

77 Lubricants  
1761 JA - The Netherlands  
T +31 (0)78 6527652  
[technical@77lubricants.nl](mailto:technical@77lubricants.nl) - [www.77lubricants.nl](http://www.77lubricants.nl)

**1.4. Emergency telephone number**

Emergency number : +31 (0)78 6527652  
Monday to Friday: 09:00 - 16:00 (CET)

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	+44 20 7188 7188	

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Skin sensitisation, Category 1 H317  
Full text of H statements : see section 16

**Adverse physicochemical, human health and environmental effects**

No additional information available

# 43110 - AUTOGEAR OIL XP 80W-90

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

Signal word (CLP) :

Warning

Hazardous ingredients :

Amines, C12-14-tert-alkyl, 2-[[bis(1,3-dimethylbutoxy)phosphinothioyl]thio]methylethyl phosphates; Polysulphides, di-tert-Bu

Hazard statements (CLP) :

H317 - May cause an allergic skin reaction.

Precautionary statements (CLP) :

P261 - Avoid breathing dust, fume, gas, mist, spray, vapours.  
P272 - Contaminated work clothing should not be allowed out of the workplace.  
P280 - Wear protective gloves, protective clothing, eye protection, face protection.  
P302+P352 - IF ON SKIN: Wash with plenty of water.  
P321 - Specific treatment (see supplemental first aid instruction on this label).  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

### 2.3. Other hazards

Other hazards not contributing to the classification :

Flammable liquids. Prolonged or repeated skin contact with the material will remove natural oils which leads to a dermatitis. Spills of this product present a serious slipping hazard.

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (Note L)	(CAS-No.) 64742-65-0 (EC-No.) 265-169-7 (EC Index-No.) 649-474-00-6 (REACH-no) 01-2119471299-27	50 – 75	Not classified
Residual oils (petroleum), solvent-dewaxed; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of ong, branched chain hydrocarbons from a residual oil by solvent crystallization. It consists of hydrocarbons having carbon numbers predominantly greater than C25 and boiling above approxi mately 400 °C (752 °F).] (Note L)	(CAS-No.) 64742-62-7 (EC-No.) 265-166-0 (EC Index-No.) 649-471-00-X (REACH-no) 01-2119480472-38	25 – 50	Not classified
Polysulphides, di-tert-Bu	(CAS-No.) 68937-96-2 (EC-No.) 273-103-3 (EC Index-No.) 01-2119540515-43 (REACH-no) 01-2119540515-43	1 – 5	Skin Sens. 1, H317 Aquatic Chronic 3, H412

# 43110 - AUTOGEAR OIL XP 80W-90

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Amines, C12-14-tert-alkyl, 2-[[bis(1,3-dimethylbutoxy)phosphinothioyl]thio]methylethyl phosphates	(CAS-No.) 141904-03-2 (EC-No.) 931-384-6 (REACH-no) 01-2119493620-38	0,5 – 2,5	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Mineral oil		0,5 – 2,5	Not classified
1,3,4-Thiadiazolidine-2,5-dithione, reaction products with hydrogen peroxide and tert-nonanethiol	(CAS-No.) 91648-65-6 (EC-No.) 293-927-7 (REACH-no) 01-2119976351-35	0,05 – 0,5	Aquatic Chronic 3, H412
O,O,O-triphenyl phosphorothioate	(CAS-No.) 597-82-0 (EC-No.) 209-909-9 (REACH-no) 01-2119979545-21	0,1 – 0,5	Aquatic Chronic 4, H413

### Specific concentration limits:

Name	Product identifier	Specific concentration limits
Amines, C12-14-tert-alkyl, 2-[[bis(1,3-dimethylbutoxy)phosphinothioyl]thio]methylethyl phosphates	(CAS-No.) 141904-03-2 (EC-No.) 931-384-6 (REACH-no) 01-2119493620-38	( 9,4 ≤C < 100) Skin Sens. 1, H317 ( 50 ≤C < 100) Eye Dam. 1, H318
O,O,O-triphenyl phosphorothioate	(CAS-No.) 597-82-0 (EC-No.) 209-909-9 (REACH-no) 01-2119979545-21	( 0 <C ≤ 0) Repr. 2, H361fd

Note L : The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method', Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3. Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Wash with plenty of water/.... If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see supplemental first aid instruction on this label). Wash contaminated clothing before reuse.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: After adequate first aid, no further treatment is required unless symptoms reappear.
Symptoms/effects after inhalation	: After adequate first aid, no further treatment is required unless symptoms reappear. May cause an allergic skin reaction.
Symptoms/effects after skin contact	: After adequate first aid, no further treatment is required unless symptoms reappear.
Symptoms/effects after eye contact	: After adequate first aid, no further treatment is required unless symptoms reappear.
Symptoms/effects after ingestion	: After adequate first aid, no further treatment is required unless symptoms reappear.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# 43110 - AUTOGEAR OIL XP 80W-90

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.  
Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.  
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Protective equipment : Eliminate all ignition sources if safe to do so.  
Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing, gloves and eye/face protection. Equip cleanup crew with proper protection.  
Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.  
Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid breathing dust/fume/gas/mist/vapours/spray.  
Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use.  
Incompatible products : Strong bases. Strong acids.  
Incompatible materials : Sources of ignition. Direct sunlight.  
Storage temperature : 50 °C  
Storage area : Store in a well-ventilated place. Store away from heat.  
Special rules on packaging : Store in a closed container. Keep only in original container.

# 43110 - AUTOGEAR OIL XP 80W-90

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Amines, C12-14-tert-alkyl, 2-[[bis(1,3-dimethylbutoxy)phosphinothioyl]thio]methylethyl phosphates (141904-03-2)

##### USA - ACGIH - Occupational Exposure Limits

ACGIH TWA (mg/m <sup>3</sup> )	5
--------------------------------	---

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)

##### EU - Occupational Exposure Limits

IOELV TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
IOELV STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>

##### Bulgaria - Occupational Exposure Limits

OEL TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
OEL STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>

##### Croatia - Occupational Exposure Limits

GVI (granična vrijednost izloženosti) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>

##### Czech Republic - Occupational Exposure Limits

Expoziční limity (PEL) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
Expoziční limity (NPK-P) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>

##### Denmark - Occupational Exposure Limits

Grænsevædi (8 timer) (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup>
---	---------------------

##### Netherlands - Occupational Exposure Limits

Grenswaarde TGG 8H (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
---	---------------------

### Mineral oil

##### EU - Occupational Exposure Limits

IOELV TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
--------------------------------	---------------------

##### Belgium - Occupational Exposure Limits

Limit value (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
Short time value (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>

##### Bulgaria - Occupational Exposure Limits

OEL TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
------------------------------	---------------------

##### Czech Republic - Occupational Exposure Limits

Expoziční limity (PEL) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
Expoziční limity (NPK-P) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>

# 43110 - AUTOGEAR OIL XP 80W-90

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Finland - Occupational Exposure Limits	
HTP-arvo (8h) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
Greece - Occupational Exposure Limits	
OEL TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
Latvia - Occupational Exposure Limits	
OEL TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
Lithuania - Occupational Exposure Limits	
IPRV (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup>
TPRV (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup>
Netherlands - Occupational Exposure Limits	
Grenswaarde TGG 8H (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
Poland - Occupational Exposure Limits	
NDS (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
NDSch (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Spain - Occupational Exposure Limits	
VLA-ED (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
VLA-EC (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Sweden - Occupational Exposure Limits	
nivågränsvärde (NVG) (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup>
kortidsvärde (KTV) (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup>
USA - ACGIH - Occupational Exposure Limits	
ACGIH TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
ACGIH STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>

## 8.2. Exposure controls

### Appropriate engineering controls:

Use adequate ventilation to keep oil mist below applicable standard. Use splash goggles when eye contact due to splashing is possible. Ocular shower with suitable liquid.

### Personal protective equipment:

Insulated gloves. Safety glasses. Protective clothing. Avoid all unnecessary exposure.

Materials for protective clothing:
Wear suitable protective clothing

Hand protection:
Wear protective gloves.

Eye protection:
Chemical goggles or safety glasses

Skin and body protection:
Wear suitable protective clothing

# 43110 - AUTOGEAR OIL XP 80W-90

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### Respiratory protection:

Wear appropriate mask

### Personal protective equipment symbol(s):



### Environmental exposure controls:

Avoid release to the environment.

### Other information:

Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: light brown.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: -27 °C
Boiling point	: No data available
Flash point	: > 190 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Non flammable.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 902,1 kg/m <sup>3</sup> @15°C
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 148,4 mm <sup>2</sup> /s @40°C
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Not established.

### 10.3. Possibility of hazardous reactions

Not established.

# 43110 - AUTOGEAR OIL XP 80W-90

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

#### 1,3,4-Thiadiazolidine-2,5-dithione, reaction products with hydrogen peroxide and tert-nonanethiol (91648-65-6)

LD50 oral (rat)	> 10000 mg/kg
LD50 dermal (rat)	> 5000 mg/kg
LC50 inhalation (rat) (Vapours - mg/l/4h)	> 2,75 mg/l/4h

**Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)**

LD50 oral (rat)	> 5000 mg/kg bodyweight
LD50 dermal (rabbit)	> 5000 mg/kg
LC50 inhalation (rat) (Vapours - mg/l/4h)	> 5,53 mg/l/4h

#### Mineral oil

LD50 oral (rat)	> 5000 mg/kg
LD50 dermal (rabbit)	> 5000 mg/kg
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5000 mg/l/4h

Skin corrosion/irritation : Not classified  
Additional information : Based on available data, the classification criteria are not met  
Serious eye damage/irritation : Not classified  
Additional information : Based on available data, the classification criteria are not met  
Respiratory or skin sensitisation : May cause an allergic skin reaction.  
Germ cell mutagenicity : Not classified  
Additional information : Based on available data, the classification criteria are not met  
Carcinogenicity : Not classified  
Additional information : Based on available data, the classification criteria are not met  
  
Reproductive toxicity : Not classified  
Additional information : Based on available data, the classification criteria are not met  
  
STOT-single exposure : Not classified  
Additional information : Based on available data, the classification criteria are not met  
  
STOT-repeated exposure : Not classified  
Additional information : Based on available data, the classification criteria are not met



# 43110 - AUTOGEAR OIL XP 80W-90

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>Amines, C12-14-tert-alkyl, 2-[[bis(1,3-dimethylbutoxy)phosphinothioyl]thio]methylethyl phosphates (141904-03-2)</b>	
NOAEL (subacute, oral, animal/male, 28 days)	500 mg/kg bodyweight
NOAEL (subacute, oral, animal/female, 28 days)	150 mg/kg bodyweight

<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)</b>	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight
NOAEL (dermal, rat/rabbit, 90 days)	≈ 1000 mg/kg bodyweight

Aspiration hazard : Not classified  
Additional information : Based on available data, the classification criteria are not met

<b>43110 - AUTOGEAR OIL XP 80W-90</b>	
Viscosity, kinematic	148,4 mm <sup>2</sup> /s @40°C

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.  
Hazardous to the aquatic environment, short-term (acute) : Not classified  
Hazardous to the aquatic environment, long-term (chronic) : Not classified

<b>O,O,O-triphenyl phosphorothioate (597-82-0)</b>	
LC50 fish 1	> 100 mg/l Brachydanio rerio
EC50 Daphnia 1	> 100 mg/l Daphnia Magna
EC50 72h algae (1)	> 100 mg/l Scenedesmus quadricauda
NOEC chronic crustacea	> 5,5 mg/l 21 DY Daphnia Magna

<b>Polysulphides, di-tert-Bu (68937-96-2)</b>	
EC50 Daphnia 1	63 mg/l Daphnia Magna
EC50 72h algae (1)	> 100 mg/l

<b>1,3,4-Thiadiazolidine-2,5-dithione, reaction products with hydrogen peroxide and tert-nonanethiol (91648-65-6)</b>	
LC50 fish 1	1000 mg/l Pimephales promelas
EC50 Daphnia 1	41 mg/l Daphnia
EC50 72h algae (1)	100 mg/l Pseudokirchneriella subcapitata

<b>Amines, C12-14-tert-alkyl, 2-[[bis(1,3-dimethylbutoxy)phosphinothioyl]thio]methylethyl phosphates (141904-03-2)</b>	
NOEC (chronic)	0,12 mg/l

# 43110 - AUTOGEAR OIL XP 80W-90

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

**Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)**

LC50 fish 1	100 mg/l
EC50 Daphnia 1	10000 mg/l
EC50 72h algae (1)	3 mg/l

### Mineral oil

LC50 fish 1	> 100 mg/l Pimephales promelas
EC50 Daphnia 1	> 10000 mg/l
EC50 72h algae (1)	> 100 mg/l Scenedesmus quadricauda

## 12.2. Persistence and degradability

### 43110 - AUTOGEAR OIL XP 80W-90

Persistence and degradability	Not established.
-------------------------------	------------------

### O,O,O-triphenyl phosphorothioate (597-82-0)

Biodegradation	18,55 (17,8 – 19,3) %
----------------	-----------------------

### Polysulphides, di-tert-Bu (68937-96-2)

Biodegradation	13 % 28 DAYS OECD TG 301 B
----------------	----------------------------

### 1,3,4-Thiadiazolidine-2,5-dithione, reaction products with hydrogen peroxide and tert-nonanethiol (91648-65-6)

Biodegradation	2 % 28 DAYS
----------------	-------------

### Amines, C12-14-tert-alkyl, 2-[[bis(1,3-dimethylbutoxy)phosphinothioyl]thio]methylethyl phosphates (141904-03-2)

Persistence and degradability	Not biodegradable.
Biodegradation	7,4 % 28 DY, OECD TG 301 B

**Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)**

Persistence and degradability	Not biodegradable.
Biodegradation	31 % 28 d OECD 301F

### Mineral oil

Biodegradation	31 %
----------------	------

## 12.3. Bioaccumulative potential

### 43110 - AUTOGEAR OIL XP 80W-90

Bioaccumulative potential	Not established.
---------------------------	------------------

### O,O,O-triphenyl phosphorothioate (597-82-0)

Bioconcentration factor (BCF REACH)	2551
Bioaccumulative potential	Bioaccumulative potential.

# 43110 - AUTOGEAR OIL XP 80W-90

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### Polysulphides, di-tert-Bu (68937-96-2)

Partition coefficient n-octanol/water (Log Kow)	6
---	---

### 1,3,4-Thiadiazolidine-2,5-dithione, reaction products with hydrogen peroxide and tert-nonanethiol (91648-65-6)

Partition coefficient n-octanol/water (Log Kow)	9,4
---	-----

### Amines, C12-14-tert-alkyl, 2-[[bis(1,3-dimethylbutoxy)phosphinothioyl]thio]methylethyl phosphates (141904-03-2)

Partition coefficient n-octanol/water (Log Kow)	9,4
---	-----

**Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)**

Bioconcentration factor (BCF REACH)	260
-------------------------------------	-----

Partition coefficient n-octanol/water (Log Pow)	9,2
---	-----

## 12.4. Mobility in soil

### O,O,O-triphenyl phosphorothioate (597-82-0)

Ecology - soil	Adsorbs into the soil.
----------------	------------------------

## 12.5. Results of PBT and vPvB assessment

No additional information available

## 12.6. Other adverse effects

Additional information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Ecology - waste materials	: Avoid release to the environment.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

### 14.1. UN number

UN-No. (ADR)	: Not applicable
UN-No. (IMDG)	: Not applicable
UN-No. (IATA)	: Not applicable
UN-No. (ADN)	: Not applicable
UN-No. (RID)	: Not applicable

### 14.2. UN proper shipping name

Proper Shipping Name (ADR)	: Not applicable
Proper Shipping Name (IMDG)	: Not applicable
Proper Shipping Name (IATA)	: Not applicable

# 43110 - AUTOGEAR OIL XP 80W-90

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Proper Shipping Name (ADN) : Not applicable  
Proper Shipping Name (RID) : Not applicable

### 14.3. Transport hazard class(es)

**ADR**  
Transport hazard class(es) (ADR) : Not applicable

**IMDG**  
Transport hazard class(es) (IMDG) : Not applicable

**IATA**  
Transport hazard class(es) (IATA) : Not applicable

**ADN**  
Transport hazard class(es) (ADN) : Not applicable

**RID**  
Transport hazard class(es) (RID) : Not applicable

### 14.4. Packing group

Packing group (ADR) : Not applicable  
Packing group (IMDG) : Not applicable  
Packing group (IATA) : Not applicable  
Packing group (ADN) : Not applicable  
Packing group (RID) : Not applicable

### 14.5. Environmental hazards

Dangerous for the environment : No  
Marine pollutant : No  
Other information : No supplementary information available

### 14.6. Special precautions for user

**Overland transport**  
No data available

**Transport by sea**  
No data available

**Air transport**  
No data available

**Inland waterway transport**  
No data available

**Rail transport**  
No data available

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions  
Contains no substance on the REACH candidate list  
Contains no REACH Annex XIV substances  
Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.  
Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

#### 15.1.2. National regulations

##### Germany

Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1)

# 43110 - AUTOGEAR OIL XP 80W-90

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

### Netherlands

Ministry's list of carcinogens : Polysulphides, di-tert-Bu,1,3,4-Thiadiazolidine-2,5-dithione, reaction products with hydrogen peroxide and tert-nonanethiol ,Residual oils (petroleum), solvent-dewaxed; Baseoil—unspecified; [A complex combination of hydrocarbons obtained by removal of ong, branched chain hydrocarbons from a residual oil by solvent crystallization. It consists of hydrocarbons having carbon numbers predominantly greater than C25 and boiling above approximately 400 °C (752 °F).],Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil—unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] are listed

Ministry's list of mutagens : Polysulphides, di-tert-Bu,1,3,4-Thiadiazolidine-2,5-dithione, reaction products with hydrogen peroxide and tert-nonanethiol ,Residual oils (petroleum), solvent-dewaxed; Baseoil—unspecified; [A complex combination of hydrocarbons obtained by removal of ong, branched chain hydrocarbons from a residual oil by solvent crystallization. It consists of hydrocarbons having carbon numbers predominantly greater than C25 and boiling above approximately 400 °C (752 °F).],Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil—unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] are listed

NON-exhaustive list of reproductive toxins - : None of the components are listed

Breastfeeding

NON-exhaustive list of reproductive toxins - Fertility : None of the components are listed

NON-exhaustive list of reproductive toxins - : None of the components are listed

Evolution

### Denmark

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product  
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose

# 43110 - AUTOGEAR OIL XP 80W-90

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
PNEC	Predicted No-Effect Concentration
PBT	Persistent Bioaccumulative Toxic
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H- and EUH-statements:	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Repr. 2	Reproductive toxicity, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

SDS EU (REACH Annex II)

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness