



# ATF TYPE F

## Product Description:

**ATF TYPE F** is a high friction automatic transmission fluid intended for use in automatic transmissions of all Ford vehicles that were built prior to 1977 and certain models built during 1977-1980 requiring fluids meeting Ford ESW-M2C33-F specification.

**ATF TYPE F** is formulated on high refined mineral base stock in combination with an unique additive package to reach the following properties.

- Extended thermal- and oxidation stability.
- Superior anti-wear technology protects transmission against wear.
- Improved low temperature fluidity provides fast circulation in cold climatic conditions.
- Compatible with all common seal materials.

**ATF TYPE F** exceeds the following performance criteria:

**FORD M2C33-F**  
**Borg-Warner**

**Ford M2C33-G**

**Ford M2C9007-AA**



Property	Unit	Test Method	Typical Value
Color		Visual	Red
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	865
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	35
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	7.2
Viscosity Index		ASTM D2270	177
Flash Point COC	°C	ASTM D92	195
Pour Point	°C	ASTM D7346	-42

**Product Nr:** 43170

**Date Superseded:** 17-02-2016

**Date Issued:** 16-12-2019

**Revision nr:** 01