



MOTOR CYCLE OIL

SYN 4T

15W-50

Product Description:

MOTOR CYCLE OIL SYN 4T 15W-50 is a high performance 4-stroke gasoline engine oil developed specifically to meet the special requirements of latest high performance air and water-cooled 4-stroke motorcycles.. It provides excellent protection to engine, gearbox and wet clutch used in 4-stroke motorcycles and ensures highest degree of reliability even under severe operating conditions and temperatures.

MOTOR CYCLE OIL SYN 4T 15W-50 is based on high quality synthetic technology Hydrocracked and hydro treated base stocks in combination with a special selected additive package to obtain the following properties.

- Outstanding thermo-oxidative stability.
- Exceptional anti-wear, anti-rust and anti-corrosion properties.
- High friction properties to eliminate clutch slippage.
- Increased power/ fuel economy and improves drivability.
- Excellent dispersancy and detergency properties.
- Excellent shear stability maintains viscosity under high temperature-high shear environment and provides improved wear protection.
- Outstanding low temperature properties enable easy starting at low ambient temperatures and ensure effective lubrication and wear protection at start up.
-

MOTOR CYCLE OIL SYN 4T 15W-50 exceeds the following performance criteria:

API SN JASO MA/MA2



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	15W-50
Density@15°C	kg/m ³	ASTM D4052	861.5
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	125.8
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	18.6
Viscosity Index		ASTM D2270	163
Viscosity CCS @-20°C, max	cP	ASTM D5293	3700
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-33
Total Base Number	mgKOH/g	ASTM D2896	8.1

Product Nr: 42975

Date Superseded: 2-2-2021

Date Issued: 7-1-2025

Revision nr: 2