



AUTOGEAR OIL MP

85W-90

Product Description:

AUTOGEAR OIL MP 85W-90 is an universal high performance mineral multi-purpose gear oil for use in manual transmission en transaxles of passenger cars, vans, light- and heavy commercial vehicles, off-highway equipment, mining and agriculture where a SAE 85W-90 GL-5 is been required.

AUTOGEAR OIL MP 85W-90 is based on high quality mineral base oil in combination with a special additive package to ensure the following properties:

- Good thermo-oxidative stability.
- Good load bearing characteristics.
- Effective rust and corrosion protection.
- High low temperature fluidity provides smoother shifting at low ambient temperatures.
- Exceptional shear stable.

AUTOGEAR OIL MP 85W-90 meets the following performance criteria:

API GL-4/5	MB 235.6	MAN 342-M1-M2	MIL-PRF-2105D
Volvo 97310	Volvo 97316	Volvo STD 1273.21	SAE J2360
SCANIA STO 1.0	ZF TE-ML 05A/07A/08/12E/16B/16C/17B/19B/21A		



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J306	85W-90
Density@15°C	kg/m³	ASTM D4052	888.3
Kin. Viscosity @40°C	mm²/s	ASTM D7042	154.8
Kin. Viscosity @100°C	mm²/s	ASTM D7042	15.9
Low-Temperature Brookfield Viscosity @ -12°	cP	ASTM D2983	13000
Viscosity Index		ASTM D2270	105
Flash Point	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-27

Product Nr: 43070
Date Superseded: 22-01-2021

Date Issued: 20-12-2024
Revision nr: 05