



AUTOGEAR OIL MP

85W-140

Product Description:

AUTOGEAR OIL MP 85W-140 is a universal high performance mineral multi-purpose gear oil for use in manual transmission en transaxles of passenger cars, vans, light- and heavy commercial vehicles, off-highway equipment, mining and agriculture where a SAE 85W-140 GL-5 is been required.

AUTOGEAR OIL MP 85W-140 is based on high quality mineral base oil in combination with a special additive package to ensure the following properties:

- Good thermo-oxidative stability.
- Good load bearing characteristics.
- Effective rust and corrosion protection.
- High low temperature fluidity provides smoother shifting at low ambient temperatures.
- Exceptional shear stable.

AUTOGEAR OIL MP 85W-140 exceeds the following performance criteria:

API GL-5

MIL-L-2105D

Volvo STD 1273.1

ZF TE-ML 05A, 07A, 08, 12E, 16C, 16D, 21A



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J306	85W-140
Density@15°C	kg/m ³	ASTM D4052	908.8
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	390.1
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	27.7
Low-Temperature Brookfield Viscosity @ -12°	cP	ASTM D2983	69000
Viscosity Index		ASTM D2270	97
Flash Point	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-15

Product Nr: 43080

Date Issued: 4-4-2025

Date Superseded: 22-1-2021

Revision nr: 04