



INDUSTRIAL GEAR OIL SYNTH 220



Product Description:

INDUSTRIAL GEAR OIL SYNTH 220 is a ultra-high performance fully synthetic industrial gear oil suitable for wind-turbines, heavy loaded closed gear boxes and circulation systems operating under extreme conditions and high temperatures.

INDUSTRIAL GEAR OIL SYNTH 220 is formulated with special selected Poly Alpha Olefine (PAO) and Ester base stocks in combination with an unique EP-additive technology to achieve the following performance.

- Outstanding load carrying capability.
- Excellent low temperature properties.
- Effective lubrication over a wide temperature range.
- Superior thermo- and oxidation stability.
- Long service intervals.
- Excellent protection against rust, wear and foaming.
- Very high demulsibility.
- Excellent corrosion and micropitting protection (both 90°C and 60°C tests of Winergy and Vestas).

INDUSTRIAL GEAR OIL SYNTH 220 exceeds the following performance criteria:

DIN 51517-3 CLP
Cincinnati Milacron P-74
AIST 224 (US Steel 224)

ISO 12925-1 CKD
David Brown S1.53.106

AGMA 9005-F16 Antiscuff
SIEMENS MD (Flender)

Property	Unit	Test Method	Typical Value
Property	Unit	Test Method	Typical Value
ISO VG Grade		ISO 3448	220
Density@15°C	kg/m ³	ASTM D4052	855.1
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	218.5
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	29.7
Viscosity Index		ASTM D2270	171
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-51
FZG Fail Load Stage, min		DIN 51354-2	12
Demulsibility @82°C	max	ASTM D1401	15

Product Nr: 44970
Date Superseded: 16-12-2019

Date Issued: 7-1-2025
Revision nr: 03